UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

":PORT DOCUMENTATION PAGE		
PORT DOCL		
		1b. RESTRICTIVE MARKINGS
AD-A220 444		3. DISTRIBUTION / AVAILABILITY OF REPORT
AD AZZO TI		Approved for public release:
		distribution unlimited.
4. PERFORMING C IGANIZATION REPORT NUMBER(S)		S. MONITORING ORGANIZATION REPORT NUMBER(5)
		ARO 22916.15-EL-A
6a. NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL	7a. NAME OF MONITORING ORGANIZATION
Dept. of Physics	(If applicable)	U. S. Army Research Office
University of Maryland 6c ADDRESS (City, State, and ZIP Code)	AN CONTRACTOR OF THE CONTRACTO	7b. ADDRESS (City, State, and ZIP Code)
-		P. O. Box 12211
College Park, Maryland 20742-4111		Research Triangle Park, NC 27709-2211
88. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER
U. S. Army Research Office	() apparation	DAA629-85-K-0052
8c. ADDRESS (Coy, State, and ZIP Code)	10 to 40	10. SOURCE OF FUNDING NUMBERS
1 0. Bex 12211		PROGRAM PROJECT TASK WORK UNIT ACCESSION NO.
F parch Triangle Park, NC 27	7709-2211	FIFCTE
11. TLE (Include Security Classification)		
Diluted Magnetic Semiconductors (unclassified)		
12. FRSONAL AUTHORS) Anderson, James R.		
13a. TYPE OF REPORT 13b. TIME COVERED 14. DATE OF REPORT (Year, Month, Dex) 15. PAGE COUNT		
16. SUPPLEMENTARY NOTATION The view, opinions and/or findings contained in this report are those		
of the author(:) and should not be construed as an official Department of the Army position,		
17. CO: \TI CODES 18, SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
Diluted Magnetic Semiconductors, Magnetization,		
Exchange, Magnetotransport, Solid State Recrystallization, Hg1-xMn, Te, Cadmium, INORGAUIC Chemistry		
19: A STRACT (Continue on reverse if necessary and identify by block number)		
Growth and physical properties of diluted magnetic semiconductors (DMS) were		
investigated. Growth included Bridgman, solid state recrystallization, and liquid phase		
epitaxy of Hg _{1-x} Mn _x T and Hg _{1-x-y} Mn _x Cd _y Te. Very uniform crystals were produced by solid state recrystallization. Physical properties studied included magnetization, optical		
response, and magnetotranspor. From magnetization, the exchange interactions among		
magnetic ions have been deduced. Modulated spectroscopy gave details of the electronic		
structure of DMT and the quality of the material was indicated by the line widths.		
Magnetotranspore, carried our in some cases to 30 T, showed a large negative magneto- resistance and subsequent increase. The Hgi-v-Mn/Cd/Te has considerable promise for		
$-\mathbf{v}_{\mathbf{v}} - \mathbf{x} - \mathbf{y}_{\mathbf{v}} + \mathbf{x} - \mathbf{y}_{\mathbf{v}}$		
mer (1-1) Manganese (1) Telluride mercure 1-1-7) Manganese (4) Cadmin Cy. Telluride		
20. D. BUTION/AVAILABILITY ABSTRACT 21. ABSTRACT SECURITY CLASSICATION		
UL ASSIFIEDAUNUMITED A SAME AS A	PT. DTIC USERS	Unclassified
22a. NA OF RESPONSIBLE INDIVIDUAL		22b. TELEPHONE (IC INDIA Area Co. 1) 22c. OFFICE SYMBOL

Final Report

Diluted Magnetic Semiconductors

Grant Number: DAAG29-85-K-0052

Author of Report: J.R. Anderson

Name of Institution: University of Maryland, College Park, Maryland

1. Forward

Diluted magnetic semiconducting (DMS) systems are compound semiconducting systems composed of cations from columns II or IV of the Periodic Table of the Elements and anions from column VI. The term magnetic refers to the fact that some of the cations are replaced by magnetic ions such as manganese, cobalt, iron, gadolinium, or europium. These systems provide an opportunity to investigate the confluence of semiconductor physics and magnetism in a single system. That is, the semiconducting properties are influenced strongly by a magnetic field and the semiconducting carriers contribute to the magnetic features. A summary of some of these properties has been given by Furdyna.¹

In the present report we describe our investigations of the responses of DMS systems to magnetic fields, light, and electric fields.

2. Report

A. Statement of the Problem Studied

This report summarizes our investigations of methods of growth and of physical properties of DMS systems. The aim of our studies was to learn how the magnetic and semiconducting properties of DMS systems are related so that the potential of these materials for application can be realized. To accomplish this we investigated Bridgman, solid-state-recrystallization, and liquid-phase-epitaxy growth,

magnetization, magnetotransport, and modulated reflectance. Our studies suggest that magnetic-field modulation may be used to enhance the device capabilities of these materials.

- B. Summary of Most Important Results
 Our most important results are summarized as follows:
- A recipe for Bridgman growth of Hg_{1-x}Mn_xTe was developed; single crystals with mobilities comparable to those of Hg_{1-x}Cd_xTe with the same energy gap have been obtained. Calibration curves making use of the ratios of the x-ray line intensities, CdLα/TeLα and MnKα/TeLα, from electron microprobe energy dispersive analysis, have been obtained for determination of the x-values in both Hg_{1-x}Cd_xTe and Hg_{1-x}Mn_xTe.²
- 2. Solid-state recrystallization growth of Hg_{1-x}Mn_xTe and Hg_{1-x}Cd_xTe produced high-quality single crystal boules of length 7 cm in which the variation of x over the central 4 cm was less than 5%. Defect densities have been estimated from transport measurements. For example, for Hg_{.875}Mn_{.125}Te the room temperature electron concentration was about 2x10¹⁶cm⁻³, a value consistent with estimates of the intrinsic density at the room temperature band gap (230 meV). At low temperatures the samples became p-type and magnetic boiloff was observed.³ Some crystals were converted to n-type by annealing in Hg vapor.
- 3. In collaboration with Dr. S.H. Shin of the Rockwell Science Center $Hg_{1-x-y}Mn_xCd_yTe$ crystals were grown by liquid phase epitaxy and the electronic structures studied by electrolyte electroreflectance and magnetotransport. This quaternary system has been developed as a promising candidate for avalanche photodiodes at wavelengths between 1.2 and 1.8 μm.^{4,5} In particular, by appropriate choices of x and y, resonance structures have been obtained at 1.55 μm. This work has been summarized in our patent on avalanche photodiodes.⁶
- 4. A new technique, mobility spectrum analysis (MSA) employs a combination of the low-field Hall signal and magnetoresistance to obtain the carrier concentration as a continuous function of mobility. As a result, we are able, without

additional assumptions, to extract the maximum amount of information from the data concerning the types of carriers contributing to the conductance and their mobilities. This approach has been shown to work well for $Hg_{1-x}Cd_xTe$ and HgTe, materials for which the energy bands are not influenced significantly by a magnetic field.^{7,8} Up to now, however, the MSA technique has not been successful for DMS systems because a magnetic field has a strong influence on the electronic structure, but work on this problem is continuing.

- 5. Magnetization studies of both II-VI and IV-VI DMS systems have shown that the dominant contributions to the magnetization are single magnetic ions and magnetic ion pairs. We have developed a model to obtain the exchange parameters for these DMS materials from a combination of high-field magnetization and low field susceptibility studies.^{9,10,11,12}
- 6. Photoreflectance has the potential to be very important for characterization of semiconducting systems because no electrical contacts are needed and the technique is nondestructive. We have developed an extremely successful double modulation experimental technique for photoreflectance. In addition, following the work of Aspnes and Frova, 13 we have derived a model that takes account of the spatial variation of the internal electric field at surfaces and interfaces and fits both the exciton structure and the Franz-Keldysh oscillations.

 Consequently we believe photoreflectance now has a fundamental basis like electroreflectance and can be applied systematically as a semiconductor characterization tool. 14
- 7. Anodization studies supplemented by surface Raman scattering are in progress. We have shown that the surface-enhanced Raman effect is a powerful tool for examining the reaction products produced during oxidation/reduction cycles at the surface of a DMS system such as Hg_{1-x}Mn_xTe.

- C. Publications and Technical Reports
- 1. Magnetization of Hg_{1-x}Mn_xTe, J.R. Anderson, M. Gorska, L.J. Azevedo, and E.L. Venturini, Phys. Rev. <u>33</u>, 4706 (1986).
- 2. Large Negative Magnetoresistance of Cd₉Mn₁Se, J.R. Anderson, W.B. Johnson, and J.K. Furdyna, Jour. Phys. Chem. Solids <u>48</u>, 481 (1987).
- 3. Phase Differences of Quantum Oscillations of the Hall Voltage, R.G. Mani and J.R. Anderson, in High Magnetic Fields in Semiconductor Physics, Springer Series in Solid-State Sciences, ed. G. Landwehr (Springer-Verlag, Berlin, 1987) Vol. 71, p. 436.
- 4. Determination of Electrical Transport Properties Using a Novel Magnetic Field-Dependent Hall Technique, W.A. Beck and J.R. Anderson, Jour. Appl. Phys., <u>62</u>, 541 (1987).
- 5. Phase Differences between Quantum Oscillations of the Magnetoresistance and Hall Effect in Hg_{1-x}Mn_xTe and Hg_{1-x}Cd_xTe, R.G. Mani, J.R. Anderson, and W.B. Johnson, Jour. Phys. Chem. Solids 48, 687 (1987).
- 6. Magnetization and Susceptibility of Pb_{1-x}Nm_xSe, M. Gorska and J.R. Anderson, Solid State Communications <u>63</u>, 1055 (1987).
- 7. Inversion Asymmetry in Hg_{1-x}Mn_xSe, J.A. Nobel, J.R. Anderson, and W.B. Johnson, Phys. Rev. <u>B36</u>, 6012 (1987).
- 8. The Magnetophonon Effect in Hg_{1-x}Cd_xTe, R.G. Mani, J.R. Anderson, J.B. Choi, and D.A. Nelson, Phys. Rev. <u>B36</u>, 9146 (1987).
- 9. Magnetic Properties of Pb_{1-x}Gd_xTe, M. Gorska, J.R. Anderson, and Z. Golacki, Mat. Res. Soc. Symp. Proc. Vol. 89, 1987 Materials Research Society, p. 119.
- Hg_{1-x-y}Mn_xCd_yTe Alloys for 1.3-1.8 μm Photodiode Applications, S.H. Shin, J.R. Anderson, W.E. Tennant, M. Gorska, C.R. Lu, and M. Fotouhi, Mat. Res. Soc. Symp. Proc. Vol. 89, 1987 Materials Research Society, p. 267.
- 11. Analysis of Multiband Conduction in HgTe by Magnetic-Field Dependent Hall Techniques, W.A. Beck, F. Crowne, J.R. Anderson, M. Gorska, and Z. Dzuiba, J. Vac. Sci. Technol. <u>A6</u>, 2772 (1988).
- 12. Influence of the Resonant Acceptor State on the Magnetotransport Properties of Zero-Gap Hg_{1-x}Mn_xTe, R.G. Mani and J.R. Anderson, Phys. Rev. <u>38</u>, 3354 (1988).
- 13. Magnetic Susceptibility and Exchange in IV-VI Diluted Magnetic Semiconductors, M. Gorska and J.R. Anderson, Phys. Rev. <u>B38</u>, 9120 (1988).
- 14. Magnetic Susceptibility of PbTe and PbSe, M. Gorska and J.R. Anderson, Acta Physica Polonica A75, 273 (1989).
- 15. Shubnikov de Haas Oscillations in HgTe/CdTe Superlattices Grown by Laser Molecular-Beam Epitaxy, Lamya Ghenim, R.G. Mani, J.R. Anderson, and J.T. Cheung. Phys. Rev. Rapid Communications <u>B39</u>, 1419 (1989).
- 16. Magneto transport on HgTe/CdTe Superlattices, Lamya Ghenim, R. Mani, J.R. Anderson, and J.T. Cheung, High Magnetic Fields in Semiconductor Physics II, Springer Series in Solid State Sciences, Vol. 87, p. 207 (1989).

- 17. The Shallow Resonant Acceptor in Semimagnetic, Zerogap Hg_{1-x}Mn_xTe, R.G. Mani and J.R. Anderson, Inst. Phys. Conf. Ser. No. 95: p. 371 (1989).
- 18. Crystal Growth of Hg_{1-x}Mn_xTe by Solid State Recrystallization, R.G. Mani, T. McNair, C.R. Lu, and R. Grober, Jour. Crystal Growth <u>97</u>, 617 (1989).
- 19. High-Field Magnetization of IV-VI Diluted Magnetic Semiconductors, J.R. Anderson, G. Kido, Y. Nishina, and M. Gorska, Phys. Rev. <u>B41</u>, 1014 (1990).
- 20. High-Field Magnetization of IV-VI Diluted Magnetic Semiconductors, J.R. Anderson, G. Kido, Y. Nishina, and M. Gorska, Semicond. Sci. Technol. 4 to be published.
- 21. Quantum Interference Effects and Weak Localization in HgTe/CdTe Superlattices Grown by Laser Molecular Beam Epitaxy, L. Ghenim, R. Mani, J.R. Anderson, and J. Cheung, Semicond. Sci. Technol. 4 to be published.
- 22. Electrolyte Electroreflectance of LPE-Grown Hg_{1-x-y}Mn_xCd_yTe, C.R. Lu, J.R. Anderson, M. Gorska, and S. Shin, Solid State Communications to be published.
- 23. HgMnCdTe Avalanche Photodiode, Soo H. Shin, J.R. Anderson, and John G. Pasko, United States Patent, Patent Number 4,862,236; 29 August 1989.
- D. Participating Scientific Personnel and Advanced Degrees Earned

R.G. Mani Ph.D.
M.M. Gorska
C.R. Lu Ph.D.
D. Streett
L. Ghenim
T. McNair
J.A. Nobel Ph.D.
W.A. Beck Ph.D.

- 3. Bibliography
- 1. J.K. Furdyna, J. Appl. Phys. <u>64</u>, R29 (1988).
- 2. J.R. Anderson, M. Gorska, L.J. Azevedo, and E.L. Venturini, Phys. Rev. 33, 4706 (1986).
- 3. R.G. Mani, T. McNair, C.R. Lu, and R. Grober, Jour. Crystal Growth 97, 617 (1989).
- 4. S.H. Shin, J.R. Anderson, W.E. Tennant, M. Gorska, and C.R Lu, Mat. Res. Soc. Symp. Proc. Vol. 89, 1987 Materials Research Society, p. 267.
- 5. C.R. Lu, J.R. Anderson, M. Gorska, and S. Shin, Solid State Communications to be published.
- 6. Soo H. Shin, J.R. Anderson, and John G. Pasko, U.S. Patent, Patent No. 4,862,236; 29 August 1989.
- 7. W.A. Beck and J.R. Anderson, Jour. Appl. Phys. <u>62</u>, 541 (1987).

- 8. W.A. Beck, F. Crowne, J.R. Anderson, M. Gorska, and Z. Dzuiba, J. Vac. Sci. Technol. A6, 2772 (1988).
- 9. M. Gorska and J.R. Anderson, Solid State Commun. 63, 1055 (1987).
- 10. M. Gorska, J.R. Anderson, and Z. Golacki, Mat. Res. Soc. Symp. Proc. Vol. 89, 1987 Materials Research Society, p. 119.
- 11. M. Gorska and J.R. Anderson, Phys. Rev. <u>B38</u>, 9120 (1988).
- 12. J.R. Anderson, G. Kido, Y. Nishina, and M. Gorska, Phys. Rev. <u>B41</u>, 1014 (1990).
- 13. D.E. Aspnes and A. Frova, Solid State Commun. 7, 155 (1969).
- 14. C.R. Lu, J.R. Anderson, M. Fotouhi, and T.F. Kuech, Effect of the Nonuniform Internal Electric Field in MBE-Grown GaAs on the Photoreflectance Line Shape submitted to Phys. Rev.